










# Copings and Sills









Manufactured from polystyrene with re-inforcing mesh and varying plaster thickness for impact resistance. Larger bands can be made up to 3.2m for more economic cutting.

Specify taper ends, are available on request for jointing the system (or order meshed only).

Back of bands can have relief cut out to hide mid floor control joints.

Available in plain polystyrene, meshed only, single coated, smooth or textured. These bands are usually rebated to fit over a block attached to the wall to prevent the band slipping down the wall.

Shape	Dimensions	Length (Metres)	Part No.
	145/30 *	2.7	CPA 145/30
	125/30	All 2.7	CPB 125/30
	155/40		CPB 155/40
	185/30		CPB 185/30
	200/60		CPB 200/60
	225/60 *		CPB 225/60
	200/80 *	All 2.7	CPC 200/80
	180/90	All 2.7	CPD 180/90
	210/155	All 2.7	CPE 210/55
	240/170		CPE 240/170
	300/150		CPF 300/150
	40/35		CPF 40/35
	210/155	All 2.7	CPG 210/155
	400/250		CPG 400/250

Shape	Dimensions	Length (Metres)	Part No.
	200/45	All 2.7	CPH 200/45
	320/35		CPH 320/35
	250/40	All 2.7	CPI 250/40
	230/80		CPI 230/80
	180/90	2.7	CPJ 180/90
	150/100	All 2.7	CPK 150/100
	250/110		CPK 250/110
	280/60	2.7	CPL 280/60
	65/55	2.7	CPM 65/55
	90/70	2.7	CPN 90/70
	160/115	2.7	CPO 160/115

\*Stock Lines

## How to Install

- Ensure that walls to which the bands are to be fixed have been properly jointed and the joints sealed
- Mark out and cut the bands to length allowing for mitres at corners.
- Mark a fixing line with a straight edge or string line
- When using rebate blocks, space these evenly along the length of the job to prevent the band slipping down the wall.
- Plaster any boxed ends
- Using Hitex Grip adhesive secure the band over rebate blocks checking against straight edge.
- Seal the top edge with Hitex sealant but leave the bottom edge unsealed.
- Lightly sand and prepare for finishing.

**Special Note:** Hitex recommend that all bands and mouldings be meshed at the joints or installed with predetermined control joints.