



Window & Mid Floor Bands & Parapet Caps

Manufactured from polystyrene with reinforcing mesh and varying layers of plaster for impact resistance. A range of sizes and designs is available. Larger bands can be made up to 3.2m long for economic cut lengths. For jointing purposes, where jointless band systems are required, specify taper ends to allow for jointing material (or order meshed only). Back of bands can have relief cut out for hiding mid floor control joints.

- Bands are available in single coated or smooth.
- Simply glued onto claddings, sealed and finish coated.
- Bands are generally flexible enough to withstand curving on site.
- Jamb bands of narrower profile butt easily onto sills and eyebrows for effect.
- Bands won't twist, bow or cup.

Shape	Dimensions	Length (Metres)	Part No.
	90/20 *	2.7	1B090/20B
	130/20 *	2.7	B130/20B
	180/20 *	2.7	B180/20B
	100/30 *	2.7	B100/30B
	150/30 *	2.7	B150/30B
	110/40	3.2	B110/40B
		90/20 *	2.7
130/20 *		2.7	B130/20S
100/30 *		2.7	B100/30S
150/30 *		2.7	B150/30S
110/40		3.2	B110/40S
		100/30 *	2.7
	185*40 *	2.7	PC185/40

* Stock Lines

How to Install

- Ensure that walls to which bands are to be fixed have been properly jointed and the joints sealed.
- Mark out and cut the band to length allowing for mitres at corners.
- Mark a fixing line using either a straight edge or string line.
- Attach the band with Hitex GRIP adhesive or equivalent.
- Ensure that the top of the band is sealed. Do not seal the bottom of the band.
- Fair in any surplus material around joints with light sanding and paint and texture the mouldings.